

Model: CUBIK URBAN CALIZA NATURE 31,6X90(A)

Codes: 100294671

Water absorption: BIII - Revestimiento (10%<=E<=20%)





| DIMENSIONAL FEATURES UNE-EN ISO 10545-2 | | | | | |
|--|-------------|----------|--|--|--|
| Thickness | 12 MM | +/-5%* | | | |
| Width | 316 MM | | | | |
| Length | 900 MM | | | | |
| Length and width deviation | Below 0.15% | +/-0.3%* | | | |
| Side straightness deviation | Below 0.15% | +/-0.3%* | | | |
| Squareness deviation | Below 0.15% | +/-0.3%* | | | |
| Surface flatness deviation | Below 0.15% | +/-0.4%* | | | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

| | MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 | |
|-----------------------------------|--|------------|
| Breaking strength | >1100 N | >600N* |
| Modulus of rupture | >23 N/MM2 | >=12N/mm2* |
| Crazing resistance | Resists 3 cycles | |
| *ISO-13006:2018 UNE-EN 14411:2016 | | |

| HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 | | | |
|--|--|---------|--|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* | |
| Stain resistance *ISO-13006:2018 UNE-EN 14411:2016 | Class 5. Easy cleaning with water | 3 Min.* | |

| *ISO-13006:2018 UNE-EN 14411:2016 | | |
|-----------------------------------|-------------------|--|
| | SCOPE OF USE | |
| Technical code-1 | Use on walls | |
| | PACKING | |
| Sales units per box | 0.853194 M2/BOX | |
| Sales units per pallet | 56.31079 M2/PAL | |
| Sales units per unit | 0.284398 M2/PIECE | |

System Certification





