

Model: ELEGANT BONE 59,6X150(A) Codes: 100303476 Water absorption: BIII - Revestimiento (10%<=E<=20%)





| DIMENSIONAL FEATURES<br>UNE-EN ISO 10545-2 |             |          |  |  |  |
|--|-------------|----------|--|--|--|
| Thickness                                  | 10.5 MM     | +/-5%*   |  |  |  |
| Width                                      | 596 MM      |          |  |  |  |
| Length                                     | 1500 MM     |          |  |  |  |
| Length and width deviation                 | Below 0.15% | +/-0.3%* |  |  |  |
| Side straightness deviation                | Below 0.15% | +/-0.3%* |  |  |  |
| Squareness deviation                       | Below 0.15% | +/-0.3%* |  |  |  |
| Surface flatness deviation                 | Below 0.15% | +/-0.4%* |  |  |  |
| *ISO-13006:2018 UNE-EN 14411:2016          |             |          |  |  |  |

| MECHANICAL FEATURES<br>UNE-EN ISO 10545-4-6-7-11 |                  |            |  |  |
|--|------------------|------------|--|--|
| Breaking strength                                | >1100            | >600N*     |  |  |
| Modulus of rupture                               | >23              | >=12N/mm2* |  |  |
| Crazing resistance                               | Resists 3 cycles |            |  |  |
| *ISO-13006:2018 UNE-EN 14411:2016                |                  |            |  |  |

| HYGIENIC FEATURES<br>UNE-EN ISO 10545-13-14:1995      |   |         |  |  |
|---|---|---------|--|--|
| Chemical resistance                                   | Class "A" for swimming pools and cleaning products<br>(resists attack). Minimum Class "B" for acids and bases | B Min.* |  |  |
| Stain resistance<br>*ISO-13006:2018 UNE-EN 14411:2016 | Class 5. Easy cleaning with water   | 3 Min.* |  |  |

| SCOPE OF USE           |                   |  |  |  |
|------------------------|-------------------|--|--|--|
| Technical code-1       | Use on walls      |  |  |  |
| PACKING                |                   |  |  |  |
| Sales units per box    | 2.681924 M2/BOX   |  |  |  |
| Sales units per pallet | 53.638477 M2/PAL  |  |  |  |
| Sales units per unit   | 0.893975 M2/PIECE |  |  |  |



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.