

Model: FIORI DI BOSCO NAT.PV6 120X120(A) Codes: 100331051 Absorption: Bla - Porcelanico (E<=0.1%)



Sistema DAPc<sup>®</sup> Declaración Ambiental de Broductor da Construcción

DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Length	1200 MM			
Thickness	6 MM			
Width	1200 MM			
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2015 UNE-EN 14411:2017				
	MECHANICAL UNE-EN ISO 105			
Breaking strenght	1118.5 N			
Modulus of rupture	43.6 N/MM2			
Crack resistance	RESISTE 3 CICLOS			
*ISO-13006:2015 UNE-EN 14411:2017				

	HYGIENIC FEATURES UNE-EN ISO 10545-13-14
Chemical resistance	MÍNIMO CLASE B
Stain resistance	CLASE 5
Resistance to thermal shock	RESISTE
*ISO-13006:2015 UNE-EN 14411:2017	

	ANTI-SLIP VALUE CEN/TS 41901/02, DIN-51130 y ASTM A137.1	
Dynamic coefficient of friction	>0.42	
Slip resistance (pendulum-wet)	CL1	
Slip resistance (pendulum-dry)	>40**	
*ISO-13006:2015 UNE-EN 14411:2017		

## SCOPE OF USE

Technical code-1 Technical code-2 Use on medium traffic floors Dry interior floors



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

## 100331051 FIORI DI BOSCO NATURE

## PORCELANOSA Grupo

PACKING				
Sales units per box	2.880184 M2/BOX			
Sales units per pallet	80.645161 M2/PAL			
Sales units per unit	1.440092 M2/PIECE			

